

Addendum

**Steven R. Ness, Rudolf A.G. de Graff, Jan Pieter Abrahams,
and Navraj S. Pannu**

In the paper “CRANK: New Methods for Automated Macromolecular Crystal Structure Solution” by Ness et al. (2004, *Structure* 12, 1753–1761), crystallographic programs were mentioned, but not included in the reference list. These programs were ARP/wARP (Perrakis et al., 1999), REFMAC (Murshudov et al., 1997), DM (Cowtan, 1994), SHELXE (Sheldrick, 2002), and SOLOMON (Abrahams and Leslie, 1996).

References

Abrahams, J.P., and Leslie, A.G.W. (1996). Methods used in the structure determination of bovine mitochondrial F1 ATPase. *Acta Crystallogr. D* 52, 30–42.

Cowtan, K. (1994). dm: an automated procedure for phase improvement by density modification. *Joint CCP4 and ESF-EACBM Newsletter on Protein Crystallography*, 31, 34–38.

Murshudov, G.N., Vagin, A.A., and Dodson, E.J. (1997). Refinement of macromolecular structures by the maximum-likelihood method. *Acta Crystallogr. D* 53, 240–255.

Perrakis, A., Morris, R., and Lamzin, V.S. (1999). Automated protein model building combined with iterative structure refinement. *Nature Struct. Biol.* 6, pp. 458–463.

Sheldrick, G.M. (2002). Macromolecular phasing with SHELXE. *Z. Kristallogr.* 217, 644–650.